

List of Tables

Table 2.1	Fit parameters to the equilibrium viscosity law, Eq. (2.1), for various metallic glass-forming liquids. It is noted that η_{∞} was assigned a value near the Planck limit which resulted in a best fit (as typically implemented when fitting viscosity).	27
Table 4.1	Physical parameters and fits for the listed glasses. T_g is the glass transition temperature as defined at 10^{12} Pa-s. G_g is the isoconfigurational shear modulus at T_g . $(n + p)$ is the combined effect of the “elastic” and “cooperative volume” fragilities as determined using Eq. 4.1. The parameter n_G is the elastic fragility index as determined from the isoconfigurational shear modulus and Eq. 4.2. The parameter p_G is found using $(n + p) - n_G$ and is the cooperative volume fragility index part of $(n + p)$. The quantity q is a measure of the relative influence of the elastic and cooperative volume fragilities, and is quantified as $q = n_G / (n + p)$.	58
Table 5.1	Changes in configurational enthalpy for each steady flow state with respect to a relaxed, undeformed reference state assessed from enthalpy recovery tests. States (i) through (iv) correspond to the strain rates indicated in Fig. 5.2 and 5.3.	84
Table 5.2	Isoconfigurational shear modulus for each steady flow state, as measured acoustically on each quenched unloaded specimen and corrected for the Debye-Grüneisen effect. States (i) through (iv) correspond to the strain rates indicated in Fig. 5.2 and 5.3. The larger errors in the measurements of $\text{Pt}_{57.2}\text{Ni}_{5.3}\text{Cu}_{14.7}\text{P}_{22.5}$ specimens are due to the use of smaller mechanical specimens, which produced a higher uncertainty in the measured density.	86